


screen 3%



SCREEN PREMIUM COLLECTION

SUPREME

Para estor enrollable y panel japonés
For roller blinds and panel tracks
Pour stores enrouleur et panneaux japonais

Para estores de rolo e painéis deslizantes
Per tende a rullo e tende a pannelli
للسنائر الدوارة واللوحات اليابانية



OUTDOOR

Uso en interiores y exteriores
Indoor and outdoor use
Utilisation intérieure et extérieure

Uso indoor e ao ar livre
Uso interno ed esterno

SCREEN PREMIUM COLLECTION
SUPREME

blanco
white

Nombre del color
Colour name

250-3% 12257001

Ancho-FA Referencia completa / Width-OF Full product code



beige
beige

250-3% 12257002



pardo
dun

250-3% 12257013



chocolate
chocolate

250-3% 12257508



gris claro
light gray

250-3% 12257003



gris medio
medium gray

250-3% 12257012
















negro
black

250-3% 12257507

SCREEN PREMIUM COLLECTION

SUPREME

Características técnicas
Technical characteristics
Caractéristiques techniques
Características técnicas
Caratteristiche tecniche
خصائص تقنية

	Peso / Weight / Poids / Peso / Peso / وزن	520 g/m² ± 10 %
	Ancho / Width / Largeur Largura / Larghezza / عرض	250 cm
	Espesor / Thickness / Épaisseur Espessura / Spessore / سماكة	0,72 mm ± 0,05
	Largo del rollo / Roll length / Longueur du rouleau Comprimento do rolo / Lunghezza del rotolo / طول اللفة	27,4 m ± 5 %
	Composición / Composition / Composition Composição / Composizione / التركيبة	73% PVC 27% polyester
	Resistente al fuego / Fire resistance Résistance au feu / Resistência ao fogo Resistente al fuoco / مقاوم النار	FR NFPA701(USA) M2 NFP92-503 B2 GB 50222-95
	Factor de Apertura / Openness Factor Facteur d'ouverture / Fator de Abertura Fattore di apertura / عامل الانفتاح	3%
	Urdimbre / Warp / Chaîne / Urdidura / Ordito Trama / Weft / Trame / Trama / Trama	36 28
	Soldable con Ultrasonido / Ultrasonic welding allowed / Soudable avec ultrasons / Soldável com ultra-som / Saldabile con ultrasuoni	
	Resistencia a la tensión / Tensile strength Résistance à la traction Resistência à tração Resistenza alla trazione قوة الشد	Urdimbre / Warp Chaîne / Urdidura Trama / Weft Trame / Trama 252 daN/5 cm 228 daN/5 cm DIN53354:1981
	Resistencia al rasgado / Tearing strength Résistance à la déchirure Resistência ao rasgamento Resistenza allo strappo مقاومة التمزق	Urdimbre / Warp Chaîne / Urdidura Trama / Weft Trame / Trama 34,6 daN 30,4 daN DIN53363:2003
	Resistencia a la luz / Light fastness Résistance à la lumière / Resistência à luz Resistenza alla luce / مقاومة الضوء	AATCC 16-2003 Class 4.5 After 80 AFU
	UV-B Factor UV-A Factor Ultraviolet Protection Factor	94,9 % 97,2 % UPF 15 AITEX STANDARD 801 2019-AN2034

OUTDOOR

Uso en interiores y exteriores
Indoor and outdoor use
Utilisation intérieure et extérieure

Uso indoor e ao ar livre
Uso interno ed esterno

Color of
the Year
2020

PANTONE®

Classic Blue
19-4052